



CDF Industries

Innovate • Fabricate • Process

Ready for Immediate Delivery

Used HZ-220

Description: High Energy Barrel Finishing

Unit Specifications:

Manufacturer: Mass Finishing Inc.

Condition: Like New

Specifications	
Main Motor	<ul style="list-style-type: none">• 15 HP Brand• Totally Enclosed• 3 Phase, 60 hertz
Barrel Rotation Motor	<ul style="list-style-type: none">• 2 HP• 230/460 Volt• 3 Phase, 60 hertz
Machine Voltage	<ul style="list-style-type: none">• 230/460 Volt
Total Capacity	<ul style="list-style-type: none">• 9.67 Cubic Feet
Approximate Shipping Weight	<ul style="list-style-type: none">• 5,200 lbs. (Machine Only)
Drive	<ul style="list-style-type: none">• Variable Frequency
Overall Dimensions	<ul style="list-style-type: none">• 75"L x 54"W x 76"H (Machine Only)• 89"L x 54"W x 90"H (With Seperator)• 100" x 95" Footprint with Drain Pan Option
Machine Construction	<ul style="list-style-type: none">• Heavy Duty Steel• All Welded Construction• Reinforced, Gusseted, and Welded to Maximum Strength
Barrel Construction	<ul style="list-style-type: none">• 27.5"L x 12"W• Four Hexogonal Barrels with Removeable Lids• Cam Locks for Secure Operation

Barrel Liners	<ul style="list-style-type: none"> • Hot Poured Polyurethane • 7/8" Thick • Field Replaceable • 11 Divider Slots, 12 Individual Chambers Possible • Divider Slots Spaced on 1" Centers
NEMA 12 Electric Control Panel	<ul style="list-style-type: none"> • UL Certification Available at Additional Cost • PLC Process Timing Control System • Power Jog of Turret
PLC Controller	<ul style="list-style-type: none"> • Store Recipes and Processes • Maintenance Reminders and Machine Diagnostics • Automated fwd/rev and Speed Adjustment
Brake System	<ul style="list-style-type: none"> • Automatically Stops the Turret When a Stop is Activated or Cycle is Completed • Activated if Door is Opened
Safety Interlock	<ul style="list-style-type: none"> • Prevents Door From Being Opened during Operation • Machine Must be Powered on in an Idle Mode to Disengage Lock • Can Only be Opened Once Cycle is Finished
Vibratory Media Separator	<ul style="list-style-type: none"> • Dump Fully Loaded Barrels Inside Machine • Media and Parts are Separated Through Screens and Vibration • Media and Parts Travel Out of Machine to Bins
Drain Pan	<ul style="list-style-type: none"> • 100"L x 79 1/2"W x 8 1/2"H • Collects any Water Drainage During Loading/ Unloading • Grip Strut Floor Surface to Prevent Operator Slip and Falls



Unit Cost:.....\$55,000.00 USD

Warranty: 1 Year

Standard Warranty Duration: Twelve (12) months from start-up date, but not more than thirteen (13) months from notification that the equipment is ready to ship. The warranty is only applicable for defects which result from normal use of the system / equipment with the required expertise, and will, in no case, exceed manufacturers' warranty policies for outside purchase items. CDF Industries will have no liability for ordinary wear and tear or if the products have been altered, misused, or damaged in any way.

THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCE WILL CDF INDUSTRIES BE LIABLE FOR INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION OR OTHER PECUNIARY LOSS FROM THE USE OR INABILITY TO USE THE PRODUCTS).

Terms & Conditions

Payment: Payment Prior to Ship

Freight: Prepay and add

Delivery: 3-5 Days

Prices Valid: 30 Days

Contact: Adam McMurtrie

Cell: 610-960-1612

E-mail: adam@cdfindustries.com